

Stockschrauben STS

mit reduziert gewaltem Holzschraubenge-
winde und gewaltem metrischem Gewinde



galv. verzinkt

Abmessung	Best.-Nr.	VE	Abmessung	Best.-Nr.	VE
M 6 X 50	191 640	100	M 10 X 90	191 698	50
M 6 X 60	191 642	100	M 10 X 100	191 700	50
M 6 X 70	191 644	100	M 10 X 120	191 702	50
M 6 X 80	191 646	100	M 10 X 130	191 703	50
M 6 X 90	191 648	100	M 10 X 140	191 704	50
M 6 X 100	191 650	100	M 10 X 160	191 706	50
M 6 X 120	191 652	100	M 10 X 180	191 708	100
M 8 X 50	191 660	100	M 10 X 200	191 710	50
M 8 X 60	191 662	100	*M 10 X 300	191 714	25
M 8 X 70	191 664	100	M 12 X 80	191 718	100
M 8 X 80	191 666	50	M 12 X 100	191 720	100
M 8 X 90	191 668	50	M 12 X 120	191 722	100
M 8 X 100	191 670	50	M 12 X 140	191 724	100
*M 8 X 110	191 672	100	M 12 X 160	191 725	50
M 8 X 120	191 674	50	M 12 X 180	191 726	50
M 8 X 140	191 676	100	*M 12 X 200	191 727	25
M 8 X 160	191 678	50	*M 12 X 250	191 728	25
M 8 X 180	191 680	50	*M 12 X 300	191 729	25
M 8 X 200	191 682	100	*M 12 X 320	191 730	1
M 10 X 50	191 690	100	*M 12 X 360	191 732	1
M 10 X 60	191 692	50	*M 12 X 400	191 734	1
M 10 X 70	191 694	50	*M 12 X 480	191 736	1
M 10 X 80	191 696	50			

*ohne Torx-Antrieb / M 10 x 300, M 12 x 320 bis M 12 x 480 kein ständiger Lagervorrat !

Handendrehgerät HED



für Stockschrauben

passend für Gewinde M 6, M 8, M 10, M 12

Abmessung	Best.-Nr.	VE
HED	191 760	1