

Spanplattenschr.



Art. 98 T

mit I-Stern, Senkkopf, geeignet für

Spanplatten, harte Hölzer und Kunststoff

Bauaufsichtliche Zulassung Z-9.1 - 729 ab 6 mm



rostfrei **A 2**

Abmessung			Best.-Nr.	VE	Abmessung			Best.-Nr.	VE		
3,0	X	16	VG	132500	2000	5,0	X	70	TG	132554	100
3,0	X	20	VG	132501	500	5,0	X	80	TG	132555	100
3,0	X	25	TG	132502	500	5,0	X	90	TG	132556	100
3,0	X	30	TG	132503	500	5,0	X	100	TG	132557	100
3,0	X	40	TG	132504	200	5,0	X	120	TG	132558	100
3,5	X	16	VG	132507	500	6,0	X	45	TG	132561	100
3,5	X	20	VG	132508	500	6,0	X	50	TG	132563	100
3,5	X	25	TG	132509	500	6,0	X	60	TG	132565	100
3,5	X	30	TG	132510	500	6,0	X	70	TG	132566	100
3,5	X	35	TG	132511	500	6,0	X	80	TG	132567	100
3,5	X	40	TG	132512	200	6,0	X	90	TG	132569	100
3,5	X	50	TG	132513	200	6,0	X	100	TG	132570	100
4,0	X	16	VG	132516	500	6,0	X	110	TG	132571	100
4,0	X	20	VG	132517	500	6,0	X	120	TG	132572	100
4,0	X	25	VG	132519	500	6,0	X	130	TG	132573	100
4,0	X	25	TG	132518	500	6,0	X	140	TG	132574	100
4,0	X	30	TG	132520	500	6,0	X	150	TG	132575	100
4,0	X	35	TG	132522	500	6,0	X	160	TG	132576	100
4,0	X	40	TG	132524	200	6,0	X	180	TG	132577	100
4,0	X	45	TG	132525	200	6,0	X	200	TG	132578	100
4,0	X	50	TG	132526	200	6,0	X	220	TG	132579	100
4,0	X	60	TG	132527	200	6,0	X	240	TG	132580	100
4,0	X	70	TG	132528	200	6,0	X	260	TG	132581	100
4,5	X	20	VG	132531	500	6,0	X	280	TG	132582	100
4,5	X	25	VG	132533	500	6,0	X	300	TG	132583	100
4,5	X	25	TG	132532	500	8,0	X	100	TG	132586	100
4,5	X	30	TG	132534	500	8,0	X	120	TG	132587	100
4,5	X	35	TG	132536	500	8,0	X	140	TG	132588	100
4,5	X	40	TG	132538	200	8,0	X	160	TG	132589	100
4,5	X	45	TG	132539	200	8,0	X	180	TG	132590	100
4,5	X	50	TG	132540	200	8,0	X	200	TG	132591	100
4,5	X	55	TG	132541	200	8,0	X	220	TG	132592	100
4,5	X	60	TG	132542	200	8,0	X	240	TG	132593	100
4,5	X	70	TG	132544	200	8,0	X	260	TG	132594	100
4,5	X	80	TG	132546	200	8,0	X	280	TG	132595	100
5,0	X	40	TG	132549	200	8,0	X	300	TG	132596	100
5,0	X	45	TG	132550	200	8,0	X	325	TG	132597	100
5,0	X	50	TG	132552	200	8,0	X	350	TG	132598	100
5,0	X	60	TG	132553	100	8,0	X	360	TG	132599	100

Bits:

TX 10 für Ø 3 - 3,5 mm

TX 25 für Ø 5 - 6 mm

TX 20 für Ø 4 - 4,5 mm

TX 40 für Ø 8 mm