

U-Scheiben

leicht, gestanzt, Stahl 140 HV
 Form A = ohne Fase / gestanzt
 Weitgehend identisch mit ISO 7089



DIN 125
 galv. verzinkt

Bolzenstärke / Loch-Ø x Außen-Ø x Stärke					Best.-Nr. Form A	VE	Bolzenstärke / Loch-Ø x Außen-Ø x Stärke					Best.-Nr. Form B	VE		
M 3	3,2	x	7	x	0,5	321260	1000	M 18	19,0	x	34	x	3,0	321296	250
M 4	4,3	x	9	x	0,8	321264	1000	M 20	21,0	x	37	x	3,0	321300	250
M 5	5,3	x	10	x	1,0	321268	1000	M 22	23,0	x	39	x	3,0	321304	250
M 6	6,4	x	12	x	1,6	321272	1000	M 24	25,0	x	44	x	4,0	321308	100
M 8	8,4	x	16	x	1,6	321276	1000	M 27	28,0	x	50	x	4,0	321312	50
M 10	10,5	x	20	x	2,0	321280	500	M 30	31,0	x	56	x	4,0	321316	25
M 12	13,0	x	24	x	2,5	321284	500	M 33	34,0	x	60	x	5,0	321320	25
M 14	15,0	x	28	x	2,5	321288	250	M 36	37,0	x	66	x	5,0	321322	25
M 16	17,0	x	30	x	3,0	321292	250	M 39	40,0	x	72	x	6,0	321324	25

6



Das Hansen-Team 2012