

# U-Scheiben

leicht, gestanz,  
Form A = ohne Fase

Weitgehend identisch mit ISO 7089



## DIN 125

rostfrei A 4

8

Bolzenstärke / Loch-Ø x Außen-Ø x Stärke			Best.-Nr.	VE	Bolzenstärke / Loch-Ø x Außen-Ø x Stärke			Best.-Nr.	VE
M 3	3,2 x 7 x 0,5	324260	1000	M 16	17,0 x 30 x 3,0	324292	200		
M 4	4,3 x 9 x 0,8	324264	1000	M 18	19,0 x 34 x 3,0	324296	200		
M 5	5,3 x 10 x 1,0	324268	1000	M 20	21,0 x 37 x 3,0	324300	200		
M 6	6,4 x 12 x 1,6	324272	1000	M 22	23,0 x 39 x 3,0	324304	200		
M 8	8,4 x 16 x 1,6	324276	500	M 24	25,0 x 44 x 4,0	324308	200		
M 10	10,5 x 20 x 2,0	324280	500	M 27	28,0 x 50 x 4,0	324312	100		
M 12	13,0 x 24 x 2,5	324284	200	M 30	31,0 x 56 x 4,0	324316	25		
M 14	15,0 x 28 x 2,5	324288	200	M 33	34,0 x 60 x 5,0	324320	25		