



Art. 906

Senkkopf, T-STAR plus
 Mit SPAX MULTI-Kopf und SPAX 4CUT-Spitze, gehärtet, gleitbeschichtet



Verzinkt, gelb passiviert

mm Ø Länge	Best.-Nr.	VE	mm Ø Länge	Best.-Nr.	VE
3,0 x 12 SG	143850	1000	4,5 x 80 TG	143924	200
3,0 x 16 SG	143852	1000	5,0 x 30 TG	143930	500
3,0 x 20 SG	143854	1000	5,0 x 35 TG	143932	500
3,0 x 25 SG	143856	1000	5,0 x 40 TG	143934	500
3,0 x 30 TG	143858	1000	5,0 x 45 TG	143936	500
3,0 x 35 TG	143860	1000	5,0 x 50 TG	143938	500
3,0 x 40 TG	143862	1000	5,0 x 60 TG	143940	500
3,5 x 16 SG	143870	1000	5,0 x 70 TG	143942	200
3,5 x 20 SG	143872	1000	5,0 x 80 TG	143944	200
3,5 x 25 SG	143874	1000	5,0 x 90 TG	143946	200
3,5 x 30 TG	143876	1000	5,0 x 100 TG	143948	200
3,5 x 35 TG	143878	1000	5,0 x 120 TG	143949	200
3,5 x 40 TG	143880	1000	6,0 x 40 TG	143950	500
3,5 x 45 TG	143882	500	6,0 x 50 TG	143952	200
3,5 x 50 TG	143884	500	6,0 x 60 TG	143954	200
4,0 x 16 SG	143890	1000	6,0 x 70 TG	143956	200
4,0 x 20 SG	143892	1000	6,0 x 80 TG	143958	200
4,0 x 25 SG	143894	1000	6,0 x 90 TG	143960	200
4,0 x 30 TG	143896	1000	6,0 x 100 TG	143962	100
4,0 x 35 TG	143898	1000	6,0 x 110 TG	143964	100
4,0 x 40 TG	143900	1000	6,0 x 120 TG	143966	100
4,0 x 45 TG	143901	500	6,0 x 130 TG	143968	100
4,0 x 50 TG	143902	500	6,0 x 140 TG	143970	100
4,0 x 60 TG	143904	500	6,0 x 150 TG	143972	100
4,0 x 70 TG	143906	500	6,0 x 160 TG	143974	100
4,5 x 30 TG	143910	1000	6,0 x 180 TG	143976	100
4,5 x 35 TG	143912	500	6,0 x 200 TG	143978	100
4,5 x 40 TG	143914	500	6,0 x 220 TG	143980	100
4,5 x 45 TG	143916	500	6,0 x 240 TG	143982	100
4,5 x 50 TG	143918	500	6,0 x 260 TG	143984	100
4,5 x 55 TG	143919	500	6,0 x 280 TG	143986	100
4,5 x 60 TG	143920	500	6,0 x 300 TG	143988	100
4,5 x 70 TG	143922	500			

8 x 80 - 10 x 400 Holzbauschrauben, Senkkopf mit I-Stern-Antrieb T 40 siehe Seite 3/13 ff. !
 Passende Torx-Bits siehe Seite 3/36 !

Bitgröße:

T10	für Ø 3 mm
T15	für Ø 3,5 mm
T20	für Ø 4 - 5 mm
T30	für Ø 6 mm



Senkkopf, T-STAR plus
 Mit SPAX MULTI-Kopf und SPAX 4CUT-Spitze, gehärtet, gleitbeschichtet
 Teilgewinde
 Verzinkt, gelb passiviert



Art. 906



mm Ø Länge	Best.-Nr. Wirox	VE	mm Ø Länge	Best.-Nr. gelb	VE
8 x 80 TG	143 800	50	10 x 80 TG	133 330	50
8 x 100 TG	143 802	50	10 x 100 TG	133 334	50
8 x 120 TG	143 803	50	10 x 120 TG	133 336	50
8 x 140 TG	143 804	50	10 x 140 TG	133 338	50
8 x 160 TG	143 805	50	10 x 160 TG	133 340	50
8 x 180 TG	143 806	50	10 x 180 TG	133 342	50
8 x 200 TG	143 807	50	10 x 200 TG	133 344	50
8 x 220 TG	143 808	50	10 x 220 TG	133 346	50
8 x 240 TG	143 809	50	10 x 240 TG	133 348	50
8 x 260 TG	143 810	50	10 x 260 TG	133 349	50
8 x 280 TG	143 811	50	10 x 280 TG	133 350	50
8 x 300 TG	143 812	50	10 x 300 TG	133 352	50
8 x 320 TG	143 813	50	10 x 320 TG	133 354	50
8 x 340 TG	143 814	50	10 x 340 TG	133 355	50
8 x 360 TG	143 815	50	10 x 360 TG	133 356	50
8 x 380 TG	143 816	50	10 x 380 TG	133 357	50
8 x 400 TG	143 817	50	10 x 400 TG	133 358	50
8 x 450 TG	143 818	50	10 x 450 TG	133 360	50
<u>U-Scheiben für 8 Ø Mehrzweckschrauben:</u>			<u>U-Scheiben für 10 Ø Mehrzweckschrauben:</u>		
8,4 x 25 x 5	133 480	50	10,5 x 33 x 6,0	133 482	50

Abmessungen M 12 x 100 bis M 12 x 600 kurzfristig lieferbar !

Bitgröße: T40 für Ø 8 mm
 T50 für Ø 10 mm

Rosetten



galv. verzinkt

Innen-Ø/ Außen-Ø/Höhe	Best.-Nr. zink	VE	Innen-Ø/ Außen-Ø/Höhe	Best.-Nr. gelb	VE
f. 5 mm/ 16 / 3	131 476	100	f. 5 mm/ 16 / 3	133 476	100
f. 6 mm/ 20 / 4,5	131 478	50	f. 6 mm/ 20 / 4,5	133 478	50
f. 8 mm/ 25 / 5	131 480	50	f. 8 mm/ 25 / 5	133 480	50
f. 10 mm/ 30 / 6	131 482	50	f. 10 mm/ 30 / 6	133 482	50
f. 12 mm/ 38 / 8	131 484	25	f. 12 mm/ 38 / 8	133 484	25