

J. Brads/Stauchkopfnägel

von 13-50 mm, Drahtmaß 1,05 x 1,25 mm



Einsatzmöglichkeiten in den Naglern der folgenden Firmen:

- BeA:** SK 325-121, SK 335-201, SK 338-616, SK 350-211
Bostitch: BT 35 CT, BT 50 CT, T 29/30, T 29/50
Haubold: SKN 30 N, SKN 30 JN 12, SKN 40 V 12
Holz Her: 3439, 3440, 3443
Paslode: FN 1835, FN 1850
Prebena: 2g-J 32 SVN, 2m-J 45 SDS, 2m-J/ES 32 Combi,
2p-J/ES 40 Combi, 2p-J 50 SDS
Senco: SLP 20, SLP 20 GLN



Abmessung	Best.-Nr. zink	VE	Abmessung	Best.-Nr. zink	VE
J 13 Cnk HA	371 740	10000	J 32 Cnk HA	371 750	5000
J 16 Cnk HA	371 742	10000	J 35 Cnk HA	371 752	5000
J 19 Cnk HA	371 744	10000	J 40 Cnk HA	371 754	5000
J 25 Cnk HA	371 746	5000	J 45 Cnk HA	371 756	4000
J 30 Cnk HA	371 748	5000	J 50 Cnk HA	371 758	4000