

Sechskantmuttern

Klasse 8

**DIN 934-8**

roh / galv. verzinkt

Abmessungen < M 5 und > M 39 = DIN 934 und identisch mit ISO 4032.

Abmessung	Best.-Nr. roh	VE	Abmessung	Best.-Nr. zink	VE
M 3	310 200	1000	M 3	311 200	1000
M 4	310 202	1000	M 4	311 202	1000
M 5	310 204	1000	M 5	311 204	1000
M 6	310 206	1000	M 6	311 206	1000
M 8	310 208	1000	M 8	311 208	1000
M 10	310 210	500	M 10	311 210	500
M 12	310 212	500	M 12	311 212	100
M 14	310 214	200	M 14	311 214	200
M 16	310 216	200	M 16	311 216	50
M 18	310 218	100	M 18	311 218	100
M 20	310 220	100	M 20	311 220	100
M 22	310 222	50	M 22	311 222	50
M 24	310 224	50	M 24	311 224	50
M 27	310 226	25	M 27	311 226	25
M 30	310 228	25	M 30	311 228	25
M 33	310 230	25	M 33	311 230	25
M 36	310 232	20	M 36	311 232	25
M 39	310 234	20	M 39	311 234	25
M 42	310 236	10			
M 45	310 238	10			
M 48	310 240	10			