## YDPU8.E204071 Tubing, Extruded Insulating Certified for Canada - Component

Page Bottom

## **Tubing, Extruded Insulating Certified for Canada - Component**

See General Information for Tubing, Extruded Insulating Certified for Canada - Component

## HONGSHANG HEAT SHRINKABLE MATERIALS CO LTD

E204071

No.8 Jinlong Rd Baolong Industrial Area, Longgang Shenzhen, Guangdong 518000 CHINA

Cat. No.	Max V, rms	Max Oper Temp, °C	Col Recognized	Oil Resistance Class* C	VW-1 Rated #
Flexible Heat Shrinkable Polyolefin tubing.					
H-2(+)	600	125	All except Clear	_	Yes
H-2(CB)	300	125	Black Only	_	Yes
H-2F(&), H-2R, H-100	600	125	All except Clear	_	Yes
H-2(ZH)(3X), H-2(HF)(3X)	600	125	All except Clear	_	Yes
H-2(ZH), H-2(HF)	600	125	All except Clear	_	Yes
Flexible (Layflat) Heat Shrinkable Polyolefin tubing.					
H-2(Z) 2PF	600	125	All except Clear	_	Yes
H-2F 2PF, H-2F 3PF	600	125	All except Clear	_	Yes
H-2R 2PF, H-2R 3PF	600	125	All except Clear	_	Yes
Heat Shrinkable Polyolefin tubing with adhesive liner.					
H-5@)	600	125	Black only	_	Yes
H-5@F	600	125	Black only	_	Yes

- (+) May be followed by suffix (Z) or (3X).
- & May be followed by suffix (X), (2X), (3X) or (4X).
- @ With meltable liner, may be followed by suffix (2X), (3X) or (4X).
- # Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked.

Note: For Cat. Nos. H-2(Z) 2PF, H-2F 2PF, H-2F 3PF, H-2R 2PF and H-2R 3PF the suffix "PF": The "P" indicates printable (not evaluated) and the "F" indicates provided flat. The number before the "PF" indicates the expansion ratio.

Marking: Company name or file number "E204071", catalog designation, voltage rating, temperature rating in degrees C, inside

<u>Questions?</u> <u>Print this page</u> <u>Terms of Use</u> <u>Page Top</u>

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".